

TENNIS COURT DETAIL SPECS: Vendor to submit with bid.

A. Deep Patching

- Material and Methods to result in a smooth monolithic underlayment to receive finishing materials.
- Surface Preparation Specifications
- Application
- MSDS Sheet for All Materials used

B. Acrylic Surface, Color Concentrate, Line Paint, Line Prime, Color (to be provided by Owner)

- Surface Preparation Specifications
- Application
- MSDS Sheets for All Materials used

C. Thoroughly cleaning scope of work:

- Courts will be thoroughly cleaned, removing all algae, dirt, asphalt, and any loose surface material
- All material cleaned off tennis courts to be taken off the premises by contractor.
- All cracks to be cleaned of all loose materials by contractor.

D. Leveling of Tennis Courts:

- All major low areas that hold water to be patched and leveled out within a nickel tolerance, if positive drainage conditions can be achieved.

E. Cracks on Tennis Courts:

- All cracks to be patched and leveled out with acrylic patching materials.

F. Material Used for Tennis Court New Surface Finishes:

- Apply one coat of World Class Acrylic Resurface material to entire surface area with an application rate of .07 undiluted gallons per yard.
- Apply two (2) texture coats of World Class Color Concentrate with an application rate of .055 gallons per square yard. The two colors to be selected by owner.
- Stripe courts with texture while line paint as per USTA regulations.

G. Net Posts and Nets:

- Refurbish existing net posts and place New Douglas TN36 nets with center tie down strap.

H. Clean-Up:

- All Job-related debris to be cleaned and taken off premises by contractor.